

DESKTOP ADAPTOR

24W~ 45W Series



DIMENTION: LxWxH=96x43x28

GENERAL SPECIFICATIONS:

Input voltage: AC 100~240V 50/60Hz

Operating Temperature: 0 40

Humidity: 5-95%RH

Storage Temperature: -20 85

Insulation Resistance: DC500V 100M (Min.)

(& between Input & Output))

Efficiency: 70%Min. At 110Vac and full load

Safety: UL,CUL,PSE,FCC,GS,CB,CE

24W Series

MODEL NO	OUTPUT VOLTAGE	OUTPUT CURRENT
GFP241DA-0540	5V	4A
GFP241DA-0638	6V	3.8A
GFP241DA-0926	9V	2.6A
GFP241DA-1024	10V	2.4A
GFP241DA-1220	12V	2A
GFP241DA-1516	15V	1.6A
GFP241DA-2410	24V	1A

36W Series

MODEL NO	OUTPUT VOLTAGE	OUTPUT CURRENT
GFP361DA-1230	12V	3A
GFP361DA-1524	15V	2.4A
GFP361DA-1623	16V	2.3A
GFP361DA-1920	19V	2.0A
GFP361DA-19A20	19.5V	2.0A
GFP361DA-2415	24V	1.5A

45W Series

MODEL NO	OUTPUT VOLTAGE	OUTPUT CURRENT
GFP451DA-1238	12V	3.8A
GFP451DA-1530	15V	3A
GFP451DA-1628	16V	2.8A
GFP451DA-1923	19V	2.3A
GFP451DA-19A23	19.5V	2.3A
GFP451DA-2419	24V	1.9A